



FPD Lithography System

# ***FX-68SH/68S***

Gen 6 Plate FPD Lithography System for  
Small-and-medium-sized High-definition Panel Production



# Gen 6 Plate FPD Lithography System for Small-and-medium-sized High-definition Panel Production

## FPD Lithography System FX-68SH/68S

The FX-68SH/68S produces leading edge small-and-medium-sized high-definition panels from Gen 6 plates. The scanner method enables improved productivity, excellent resolution and high overlay accuracy. The FX-68SH also achieves high productivity and a high resolution of  $1.2\ \mu\text{m}^{\ast 1}$ .

### Key Features

#### • Multi-lens System

The FX-68SH/68S features the multi-lens system consisting of multiple projection lenses. This design enables a wide exposure field and excellent resolution.

#### • High Resolution

While succeeding our well-known multi-lens system, Nikon has developed a new i-line projection lens that enables higher resolution. In addition, we developed an innovative correction system that takes advantage of our multi-lens system in large plate exposure. In this correction system, the focal surface follows inclination changes in a plate. This enables the high volume production of panels with a high resolution of  $1.2\ \mu\text{m}^{\ast 1}$  (L/S) in Gen 6 plates.

#### • High Overlay Accuracy

The new interferometer system for position measurement is designed to realize high overlay accuracy by enhancing measurement accuracy and position control performance.

#### • High Throughput

With the new projection lens and stage, the FX-68SH/68S achieves a high throughput of 85 plates per hour by enabling 4-scan on a Gen 6 plate.


#### • Improved Exposure Performance

The FX-68SH/68S employs a variety of calibration functions developed utilizing our unique technology and provides enhanced exposure performance stability.

### Performance

	FX-68SH	FX-68S
Resolution (L/S)	$1.2\ \mu\text{m}^{\ast 1}$ (i-line)	$1.5\ \mu\text{m}$ (i-line)
Projection magnification	1:1	
Overlay	$\leq \pm 0.27\ \mu\text{m}$	
Plate size	1,500 mm × 1,850 mm	
Takt time	42 s/plate Conditions: 1,500 mm × 1,850 mm, 4 scans, i-line, 30 mJ/cm <sup>2</sup>	

<sup>\ast 1</sup> When using a phase shift mask



#### WARNING

TO ENSURE CORRECT USAGE, READ THE CORRESPONDING MANUALS CAREFULLY BEFORE USING YOUR EQUIPMENT.

All of the products in this brochure are under export restriction. The export of these products is controlled by Japanese Foreign Exchange and Foreign Trade and International export control regime. They shall not be exported without authorization from the appropriate government authorities.

Performance and equipment are subject to change without any notice or obligation on the part of the manufacturer.  
Products and brand names are trademarks or registered trademarks of their respective companies. July 2024  
©2024 NIKON CORPORATION

<https://www.nikon.com/business/fpd/>

#### Nikon Corporation Precision Equipment Group Marketing Department

1-5-20, Nishioi, Shinagawa-ku, Tokyo 140-8601, Japan  
Tel: +81-3-6743-5533

#### Nikon Precision Korea Ltd.

2, Singal-ro 124beon-gil, Giheung-gu, Yongin-si, Gyeonggi-do, 16968 Korea  
Tel: +82-31-288-5601

#### Nikon Precision Taiwan Ltd.

3F.-1, NO.28, Taiyuan Street, Zhubei City, Hsinchu County 302, Taiwan, R.O.C.  
Tel: +886-3-552-5888

#### Nikon Precision (Shanghai) Co., Ltd.

11-12F, Tower 5, Crystal Plaza No. 36, Ping Jia Qiao Road, Pudong New District, Shanghai 200126, China  
Tel: +86-21-5899-0266